




Mercedes-Benz

Form 5116T, 09/06
Supersedes 5116T, 07/05

RX DC MKS Compliant Alignment Lift ***Approved For Mercedes-Benz USA Dealers***

**Engineered to Meet the
Specific Requirements for
Aligning Mercedes-Benz
Vehicles**



RX DC shown with HTA-MB-R Aligner, DSP600 Sensors and other optional accessories.

Large Capacity Lift With a Small Footprint

Hunter's RX DC Alignment Lift combines a 158" (4013 mm) four-wheel alignment wheelbase, 24" (610 mm) runway width and 11,000-lb. (5000 kg) capacity to provide full-service capability for a wide range of Mercedes-Benz vehicles.


- Multi-service use, clear service access all the way to the rear of the vehicle
- Locks at any of 18 heights, with a maximum 68" (1727 mm) runway height
- Fully equipped for four-wheel alignment



Extra-wide 24" runways handle a wide variety of vehicles, including the new Maybach.

HUNTER
Engineering Company

RX DC Scissor Lift



RX DC shown with optional second swing air jack.

The RX DC Lift Rack may be flush mounted for maximum ground clearance.

Model RX DC-P

- 1 Integral Harting rack wiring kit.
- 2 PowerSlide locking mechanism secures full-floating, 80" (2032 mm) long rear wheel slip plates once alignment measurements have been collected. Saves time by no longer requiring trips around lift to secure the rear slip plate pins.
- 3 Includes Mercedes-Benz compliant MKS alignment sensor brackets (set of four).
- 4 Two-stage, heavy-duty gusseted rear ramps automatically flip up to act as wheel stops. Low approach angle for low-ground clearance vehicles (e.g., SLR model). Wheel rollers won't damage floor.
- 5 Louvered ramps help prevent wheel spin and are more effective in wet weather than diamond tread or abrasive strip designs.
- 6 One standard 6,000-lb. (2724 kg) capacity swing air jack adds capability of lifting vehicles off runways during alignment procedures. Includes one center-lift jack adaptor and built-in air kit.
- 7 Built-in rub rails add drive-on confidence.
- 8 Extra-wide 24" (610 mm) runways provide easy vehicle positioning.

Visit our Website at www.hunter.com

HUNTER
Engineering Company

11250 Hunter Drive, Bridgeton, MO 63044
800-448-6848 • 314-731-3020 • FAX: 314-731-1776

RX DC Lift Specifications:

Maximum Vehicle Gross Weight:	11,000 lbs. (5,000 kg)
Maximum Wheelbase	
– General Service:	175" (4445 mm)
– 2-Wheel Alignment:	161" (4089 mm)
4-Wheel Alignment Range	
Maximum:	158" (4013 mm)
Minimum:	88" (2235 mm)
Tread Width	
– Minimum Inside Tires:	40" (1016 mm)
– Maximum Outside Tires:	88" (2235 mm)
Alignment Height:	Any 18 lock positions
Maximum Height:	68" (1727 mm)
Electrical Requirements:	208-230 volt, 1-ph, 60 Hz, 22A
Air Requirements:	90-120 psi

Standard Equipment:

- (1) 6,000-lb. capacity swing air jack, #133-69-1
- (2) Moveable worksteps*
- Front wheel stops
- Center-lift jack adaptor #20-1591-1
- (2) Wheel chocks
- Air line kit

*(Except (-P) Flush Mount Models)

Options:

(1) 6,000-lb. Capacity Swing Air Jack is standard. Other jacks may be substituted and/or a second jack of any type may be added.

- 133-69-1** 6,000-lb. Capacity Swing Air Jack
- 133-67-1** 4,500-lb. Capacity Swing Air Jack
- 133-63-1** 4,500-lb. Capacity Air-Actuated Power Jack

Because of continuing technological advancements, specifications, models and options are subject to change without notice.